



**SPECIFICATIONS**

OPERATING VOLTAGE: 6-24 volts

OPERATING TEMP.: -25 to +100°C

Extreme 140°C max. 1 hr.

STORAGE TEMP.: -30 to +100°C

Extreme 160°C max. 1 hr.

SAFE VIBRATION STRESS:

Amplitude: ±0.25mm from 20 Hz to 100 Hz

Acceleration: 10 g from 100 Hz to 1000 Hz

Usage parameters for higher vibration stress must be determined by tests.

ALL 150 PSI w/  
10-180 OHMS  
SINGLE STATION

**VDO INSTRUMENTS, INC.**

980 Brooke Road, P.O. Box 2897, Winchester, VA 22601  
Telephone (703) 665-0100 • Telex: TWX 710-833-0735

**PRESSURE SENDER  
Standard Ground**

**VERSION 2**

**0-150 PSI  
(0-10 Kp/cm<sup>2</sup>)**

PART NO.	THREAD	**
1 521 001 064	M 10 x 1K	Stud
1 521 001 071	M 12 x 1.5	Stud
1 521 001 112	M 14 x 1.5	Stud
1 521 001 174*	M 18 x 1.5	Stud
1 521 001 088	1/4" - 18 NPTF	Stud
1 521 001 143*	M 16 x 1.5	Stud
1 521 001 198*	R 1/2" DIN 2999	Stud
1 521 001 040	1/2" - 27 NPTF	Stud

\*SPECIAL ORDER

150 PSI

