

COMPOSITE TOOLS

CM



STANLEY TAPE MEASURE
This 12 foot steel tape measure, with 1/2" blade, is graduated in tenths and hundredths of inches and also in fractions of inches (32nds). Very handy for all aircraft construction. A "must" for composite construction.
No. 33-272.....P/N 33-272



STANLEY UTILITY KNIFE
Aluminum, die-cast in two sections - provides blade storage. Has handy hang hole. Furnished with No. 11-921 blade and blade guard.
No. 10-099.....P/N 10-099



NIFE BLADE
Type utility knife blade for No. 10-099 knife and knives.
P/N 11-921



HOOK BLADE
For use with No. 10-099 knife and most other makes of utility knives to cut linoleum, roofing material, cartons, etc., without damage. The razor-sharp hooked ends cut to full thickness in one stroke.
No. 11-961 Pkg. of 5 Blades
P/N 11-961



SINGLE-EDGE RAZOR BLADES
Used for trimming rough edges of laminates.....P/N 01-24904/ea.
Box of 100 30% Discount.



SPRING CLAMPS
Heavy-gauge steel clamps with vinyl grips and tips to prevent marring work. Jaws specially formed to hold flat or round objects. Two sizes available:
No. 3202-HT - Jaw Opening 2", Length 6"
P/N 12-03778



X-ACTO TOOLS
X-ACTO BLADE NO. 11
Classic fine point blade. A general purpose blade. Package of 5
P/N 01-16500



STRAIGHT EDGE
A 6-ft. long kiln-dried spruce board, 7/8" to 1" thick and 3" to 4" wide, used for checking the straightness of flying surfaces during composite construction....P/N 01-25900



6" STEEL RULER
Flexible stainless steel rule graduated in 10ths and 100ths on one side and in quick-reading 32nds and 64ths on the other side.
6 inch.....P/N 616
12 inch.....P/N 12-02062



FELT TIP MARKERS
Used for marking locations on fiberglass throughout construction.
P/N 01-26000



12" LONG DRILL BITS

For use with standard electric drill for hard-to-reach jobs.
3/32" (.094" Dia.)P/N 12-05200
1/8" (.125" Dia)P/N 12-05300
3/16" (.188" Dia)P/N 12-05400
#10 (.1935" Dia.)P/N 12-05500
1/4" Dia.....P/N 12-05600



RUBBER SEALANT
No. 732 RTV general-purpose, clear, one-part silicone rubber. Cures to a firm silicone rubber in 24 hours at room temperature.
4.7 Oz. TubeP/N 09-27800



JIFFY MIXER
This is a very effective 2-1/2" diameter stainless steel mixer on a 15" shaft. Attach to an air drill for fast, efficient mixing of larger batches. It will not dig into or gouge the sides or bottom of your mixing container.
P/N 01-00395



CALRAD VARIABLE VOLTAGE CONTROL
A fine quality control to supply the electrical current for hot-wire cutting of styrofoam and PVC foam. One unit can serve to build many aircraft. Input 115 volts AC Output variable from 0 to 130 volts AC at 5 amps Caution - fuse should be inserted in the secondary to protect the control in the event of a short circuit.
Input: 117V AC 60Hz 3-Prong AC cord. Output: 0-130V AC Adj. 60Hz; volt meter, power jack. Fuse Protection AGC: 5 Amp. Max: 500VA
P/N 01-01294