

• Made of high-strength type 4037 or 8740 alloy steel

- Centerless ground & threaded
- Minimum tensile strength 125,000 PSI
- Cadmium plated per spec QQ-P-416A, Type II, Class 3
- 431 Stainless steel (CRES)

ANX(C or H)-X(A) H = DRILLED HEAD AN = DIAMETER C = CORROSION RESISTANT STEEL A = UNDRILLED SHANK







**FOR UNDRILLED** 

**UNDRILLED** 

**FOR DRILLED SHANK NO LETTER EXAMPLE!** AN6 - 10




**FOR DRILLED HEAD** ADD "H" AND "A" **EXAMPLE:** AN6H-10A



**HEAD ONLY** DRILLED

**FOR DRILLED HEAD AN** SHANK ADD "H" ONLY EXAMPLE: **AN6H-10** 



**BOTH HEAD AND SHANK DRILLED** 

			(-) INDICATES SHANK CORROSION RESISTANT									
	Bolts are sold "EACH" ALL BOLTS		AN3					AN4				
,				Cadmium Plated AN3 (10-32)		Stainless AN3C (10-32)			Cadmium Plated AN4 (1/4-28)		Stainless AN4C (1/4-28)	
	Dash No.	Nominal Length	Grip Length	Drilled Price	Undrilled "A" Price	Drilled Price	Undrilled "A' Price	Grip Length	Drilled Price	Undrilled "A" Price	Drilled Price	Undrilled "A" Price
	-3	15/32	1/16					1/16				
1	-4	17/32	1/8					1/16				
=	-5	21/32	1/4					3/16				
	-6	25/32	3/8					5/16				
	-7	29/32	1/2					7/16				
	-10	1-1/32	5/8					9/16				
	-11	1-5/32	3/4					11/16				
	-12	1-9/32	7/8					13/16				
	-13	1-13/32	1					15/16				
	-14	1-17/32	1-1/8					1-1/16				
	-15	1-21/32	1-1/4					1-3/16				
<b>.</b>	-16	1-25/32	1-3/8			-		1-5/16			-	
•	-17	1-29/32	1-1/2					1-7/16				
	-20	2-1/32	1-5/8					1-9/16				
	-21	2-5/32	1-3/4			-		1-11/16			-	
	-22	2-9/32	1-7/8			-		1-13/16			-	
	-23	2-13/32	2			-		1-15/16			-	
	-24	2-17/32	2-1/8					2-1/16			-	
	-25	2-21/32	2-1/4			_		2-3/16			-	
	-26	2-25/32	2-3/8			-		2-5/16			-	
	-27	2-29/32	2-1/2			-		2-7/16			-	
	-30	3-1/32	2-5/8			-		2-9/16			-	
	-31	3-5/32	2-3/4			_	-	2-11/16			-	_
	-32	3-9/32	2-7/8			_	_	2-13/16				_
•	-33	3-13/32	3				_	2-15/16			-	_
•	-34	3-17/32	3-1/8			_	-	3-1/16				_
	-35	3-21/32	3-1/4			_		3-3/16			-	_
	-36	3-25/32	3-3/8				_	3-5/16				_
	-37	3-29/32	3-1/2			-	-	3-7/16			-	_
	-40	4-1/32	3-1/2			-	-	3-9/16			-	_
	-41	4-5/32	3-3/4				_	3-11/16			-	_
	-42	4-9/32	3-7/8			-	-	3-13/16			-	_
	-43	4-13/32	4					3-15/16				-
ID	- <del>4</del> 3	4-13/32	4-1/8					4-1/16				
	- <del>44</del> -45	4-17/32	4-1/4				-	4-1/16			-	
	-45 -46	4-21/32	4-1/4			-	-	4-5/16			-	-
	-47	4-29/32	4-3/6					4-7/16				i
		5-1/32	4-1/2			-	-	4-7/16			<u> </u>	-
	-50 -51	5-1/32	4-3/4			-	-	4-9/16			<u> </u>	-
∄	-51 -52	5-9/32	4-3/4					4-11/16				<del>-</del> -
				-		-	-				<u> </u>	-
	-53 -54	5-13/32 5-17/32	5 5-1/8	-	-	-	-	4-15/16 5-1/16	-			-
		i										
	-55 -56	5-25/32	5-1/4	-		-	<u>-</u>	5-3/16 5-5/16			-	-
	-56	5-25/32	5-3/8			-	-	5-5/16			-	-
	-57	5-29/32	5-1/2	-		-	-	5-7/16			-	-
	-60	6-1/32	5-5/8				-	5-9/16			-	

Quantity discount on AN4 bolts - 15% discount on qty of 50-99 • 20% discount on qty of 100+