

MACHINE SCREWS

MS24693 & MS24693C MACHINE SCREWS



FORMERLY AN 507)

These non-structural screws have a 100° countersunk flat head. Cadmium plated, Type 2, Class 3. Tensile strength 55,000 PSI. For both CAD plated and Stainless MS24693C are stainless steel.

Thread	Length	MS24693 Cad Plated P/N	Price Each	MS24693C Stainless P/N	Price Each
4-40	3/8	MS24693S4	---	MS24693C4	---
	7/16	MS24693S5	---	---	---
	1/2	MS24693S6	---	MS24693C6	---
	5/8	MS24693S7	---	MS24693C7	---
	1	MS24693S10	---	MS24693C10	---
6-32	1/4	MS24693S24	---	MS24693C24	---
	3/8	MS24693S26	---	MS24693C26	---
	7/16	MS24693S27	---	MS24693C27	---
	1/2	MS24693S28	---	MS24693C28	---
	5/8	MS24693S29	---	MS24693C29	---
	3/4	MS24693S30	---	MS24693C30	---
	7/8	MS24693S31	---	---	---
	1	MS24693S32	---	MS24693C32	---
	1-1/2	MS24693S36	---	---	---
	2	MS24693S40	---	---	---
8-32	1/4	MS24693S46	---	MS24693C46	---
	3/8	MS24693S48	---	MS24693C48	---
	7/16	MS24693S49	---	MS24693C49	---
	1/2	MS24693S50	---	MS24693C50	---
	5/8	MS24693S51	---	MS24693C51	---
	3/4	MS24693S52	---	MS24693C52	---
	7/8	MS24693S53	---	---	---
	1	MS24693S54	---	MS24693C54	---
	1-1/4	MS24693S56	---	MS24693C56	---
	1-1/2	MS24693S58	---	---	---
	2	MS24693S62	---	---	---
	10-32	1/4	MS24693S268	---	MS24693C268
3/8		MS24693S270	---	MS24693C270	---
7/16		MS24693S271	---	MS24693C271	---
1/2		MS24693S272	---	MS24693C272	---
5/8		MS24693S273	---	MS24693C273	---
3/4		MS24693S274	---	MS24693C274	---
1		MS24693S276	---	MS24693C276	---
1-1/4		MS24693S278	---	MS24693C278	---
1-1/2		MS24693S280	---	---	---
2		MS24693S284	---	---	---
2-1/2		MS24693-S286	---	---	---
1/4-28		7/16	---	---	MS24693C293
	1/2	MS24693S294	---	MS24693C294	---
	5/8	MS24693S295	---	MS24693C295	---
	3/4	MS24693S296	---	---	---
	1	---	---	MS24693C298	---

AN526 MACHINE SCREWS

Truss-head non-structural machine screws made of carbon steel, cadmium plated. Minimum tensile strength 55,000 PSI. Available in slot head or Phillips recessed head.

Thread	Length	Phillips Part No.	Price Each	Slotted Part No.	Price Each
4-40	1/4	AN526-440R4	---	----	---
	3/8	AN526-440R6	---	----	---
	1/2	AN526-440R8	---	----	---
	1	AN526-440R16	----	----	---
6-32	1/4	AN526-632R4	---	----	---
	5/16	AN526-632R5	---	----	---
	3/8	AN526-632R6	---	AN526-632-6	---
	7/16	AN526-632R7	---	----	---
	1/2	AN526-632R8	---	AN526-632-8	---
	9/16	AN526-632R9	---	----	---
	5/8	AN526-632R10	---	AN526-632-10	---
	3/4	AN526-632R12	---	AN526-632-12	---
	7/8	AN526-632R14	---	----	---
	1	AN526-632R16	---	----	---
	1-1/2	AN526-632-R24	---	----	---
	2	AN526-632R32	---	----	---
8-32	1/4	AN526-832R4	---	----	---
	5/16	AN526-832R5	---	----	---
	3/8	AN526-832R6	---	----	---
	7/16	AN526-832R7	---	----	---
	1/2	AN526-832R8	---	AN526-832-8	---
	9/16	AN526-832R9	---	----	---
	5/8	AN526-832R10	---	---	---
	3/4	AN526-832R12	---	AN526-832-12	---
	7/8	AN526-832R14	---	----	---
	1	AN526-832R16	---	AN526-832-16	---
	1-1/4	AN526-832-R20	---	----	---
	1-1/2	AN526-832-R24	---	----	---
10/32	1/4	AN526-1032R4	---	----	---
	5/16	AN526-1032R5	---	----	---
	3/8	AN526-1032R6	---	----	---
	7/16	AN526-1032R7	---	----	---
	1/2	AN526-1032R8	---	----	---
	9/16	AN526-1032R9	---	----	---
	5/8	AN526-1032R10	---	AN526-1032-10	---
	3/4	AN526-1032R12	---	AN526-1032-12	---
	7/8	AN526-1032R14	---	AN526-1032-14	---
	1	AN526-1032R16	---	----	---
	1-1/8	AN526-1032R18	---	----	---
	1-1/4	AN526-1032R20	---	----	---
	1-1/2	AN526-1032R24	---	----	---
	1-3/4	AN526-1032R28	---	----	---
	2	AN526-1032R32	---	----	---

HA