

ALLOY/STRUCTURAL — MACHINE SCREWS

NAS600 - NAS603 MACHINE SCREWS



- Phillips Pan Head
- Alloy Steel (8740)
- Finish - Cadmium per QQ-P-416
- Tensile - 160,000 - 180,000 PSI

Thread	Length	Part No.	Price Ea.
4-40	.188	NAS600-3P	---
	.250	NAS600-4P	---
	.312	NAS600-5P	---
	.375	NAS600-6P	---
	.438	NAS600-7P	---
	.500	NAS600-8P	---
6-32	.188	NAS601-3P	---
	.250	NAS601-4P	---
	.312	NAS601-5P	---
	.375	NAS601-6P	---
	.438	NAS601-7P	---
	.500	NAS601-8P	---
	.562	NAS601-9P	---
	.625	NAS601-10P	---
8-32	.750	NAS601-12P	---
	.188	NAS602-3P	---
	.250	NAS602-4P	---
	.312	NAS602-5P	---
	.375	NAS602-6P	---
	.438	NAS602-7P	---
	.500	NAS602-8P	---
	.562	NAS602-9P	---
	.625	NAS602-10P	---
	.688	NAS602-11P	---
	.750	NAS602-12P	---
	.813	NAS602-13P	---
.875	NAS602-14P	---	
1.00	NAS602-16P	---	
10-32	.250	NAS603-4P	---
	.312	NAS603-5P	---
	.375	NAS603-6P	---
	.438	NAS603-7P	---
	.500	NAS603-8P	---
	.562	NAS603-9P	---
	.625	NAS603-10P	---
	.688	NAS603-11P	---
	.750	NAS603-12P	---
	.813	NAS603-13P	---
	.875	NAS603-14P	---
	.938	NAS603-15P	---
	1.00	NAS603-16P	---
	1.125	NAS603-18P	---
	1.25	NAS603-20P	---

NAS1202 / NAS1203 FLUSH HEAD SCREWS



- Phillips 100° Flat Head
- Tensile - 160,000 - 180,000 PSI
- Alloy Steel Per MIL-S-6049
- Finish - Cadmium per QQ-P-416, Type II

Thread	Grip	Length	Part No.	Price Ea.
8-32	.125	.401	NAS1202-2	---
	.188	.464	NAS1202-3	---
	.250	.526	NAS1202-4	---
	.312	.588	NAS1202-5	---
	.375	.651	NAS1202-6	---
	10-32	.125	.401	NAS1203-2
.188		.464	NAS1203-3	---
.250		.526	NAS1203-4	---
.312		.588	NAS1203-5	---
.375		.651	NAS1203-6	---
.438		.714	NAS1203-7	---
.500		.776	NAS1203-8	---

MS51959 MACHINE SCREWS



- Phillips 82° Flat Head
- Stainless Steel

Thread	Length	Part No.	Each
2-56	.188	MS51959-2	---
	.250	MS51959-3	---
	.312	MS51959-4	---
	.375	MS51959-5	---
	.250	MS51959-13	---
4-40	.312	MS51959-14	---
	.375	MS51959-15	---
	.438	MS51959-16	---
	.500	MS51959-17	---
6-32	.312	MS51959-27	---
	.375	MS51959-28	---
	.438	MS51959-29	---
	.500	MS51959-30	---
	.625	MS51959-31	---
	8-32	.375	MS51959-43
.438		MS51959-44	---
.500		MS51959-45	---
.625		MS51959-46	---
.750		MS51959-47	---

HA