

# STRATOFLEX HOSE & FITTINGS



## STRATOFLEX 111 HOSE

Part No	Tube O.D.	Hose ID.	Max Press	Wt Per lb./In.	Price Per Ft.
111-4	.250	.188	3000	.0120	---
111-5	.312	.250	3000	.0130	---
111-6	.375	.312	2000	.0190	---
111-8	.500	.406	2000	.0220	---
111-10	.625	.500	1750	.0310	---
111-12	.750	.625	1500	.0380	---
111-16	1.00	.875	800	.0368	---

## STRATOFLEX 300 STRAIGHT FLARED FITTINGS FOR 111 HOSE



Part No.	Tube O.D.	Thread	Price Ea.
300-3S	.188	3/8-24	---
300-4S	.200	7/16-20	---
300-5S	.312	1/2-20	---
300-6S	.375	9/16-18	---
300-8D	.500	3/4-16	---
300-10D	.625	7/8-14	---
300-12D	.750	1-1/16-12	---
300-16D	1.00	1-5/16-12	---

## STRATOFLEX 124 HOSE



Description	Part No.	Price
124-3 Hose	124-3	---
124-4 Hose	124-4	---
124-6 Hose	124-6	---
124-8 Hose	124-8	---
124-10 Hose	124-10	---

## STRATOFLEX 156 MEDIUM PRESSURE HOSE



Part No	Tube O.D.	Hose ID.	Max Press	Mini Blend	Price/Ft.
156-3	.188	.156	1500	1.75	---
156-4	.250	.219	1500	2.00	---
156-5	.312	.281	1500	2.25	---
156-6	.375	.344	1500	2.50	---
156-8	.500	.438	1250	3.50	---
156-10	.625	.562	1250	4.00	---
156-12	.750	.688	1250	4.50	---
156-16	1.000	.875	1000	5.50	---

## STRATOFLEX 678 45° ELBOW FLARED FITTINGS FOR 156 HOSE



Part No.	Tube O.D.	Thread	Price Ea.
678-3S	.188	3/8-24	---
678-4S	.250	7/16-20	---
678-6D	.375	9/16-18	---
678-8D	.500	3/4-16	---
678-10D	.625	7/8-14	---
678-12D	.750	1-1/16-12	---



## STRATOFLEX 193 HOSE

**Specifications:** Hose meets or exceeds the requirements of MIL-H-5593. Construction: Tube - Seamless Buna - N. Reinforcement - One braid of high tensile fiber cord. Cover - Synthetic rubber. Identification: LP-MIL-H-5593-size, date of manufacture, manufacturer's code (CAGE) marked on one side of the hose. Stratoflex 193-size marked on other side of hose. Yellow markings are repeated every 12 inches. Application: Low pressure air and vacuum instrument systems. Vacuum service 20"Hg sizes -2 thru -6; 10"Hg sizes -8and -10. Temperature range: -65 to +165°F / (-54 to +74°C).

manufacturer's code (CAGE) marked on one side of the hose. Stratoflex 193-size marked on other side of hose. Yellow markings are repeated every 12 inches. Application: Low pressure air and vacuum instrument systems. Vacuum service 20"Hg sizes -2 thru -6; 10"Hg sizes -8and -10. Temperature range: -65 to +165°F / (-54 to +74°C).

Part No	Tube O.D.	Hose ID.	Max Press	Weight per In. (l.b.)	Price Per Ft.
193-2	.35	.125	300	.0038	---
193-3	.41	.188	250	.0050	---
193-4	.48	.250	200	.0058	---
193-6	.60	.375	150	.0079	---
193-8	.75	.500	150	.0115	---
193-10	.87	.625	150	.0138	---

## STRATOFLEX 646/640 45° ELBOW FLARED FITTINGS FOR 111 HOSE



Part No.	Tube O.D.	Thread	Price Ea.
646-4S	.250	7/16-20	---
646-6S	.375	9/16-18	---
646-8D	.500	3/4-16	---
646-10D	.625	7/8-14	---
640-12D	.750	1-1/16-12	---
640-16D	1.00	1-5/16-12	---

## STRATOFLEX 649/643 90° ELBOW FLARED FITTINGS FOR 111 HOSE



Part No.	Tube O.D.	Thread	Price Ea.
649-4S	.250	7/16-20	---
649-6S	.375	9/16-18	---
649-8D	.500	3/4-16	---
649-10D	.625	7/8-14	---
649-12D	.750	1-1/16-12	---

## STRATOFLEX 676 STRAIGHT FLARED FITTINGS FOR 156 HOSE



Part No.	Tube O.D.	Thread	Price Ea.
676-3S	.188	3/8-24	---
676-4S	.250	7/16-20	---
676-5S	.312	1/2-20	---
676-6D	.375	9/16-18	---
676-8D	.500	3/4-16	---
676-10D	.625	7/8-14	---
676-12D	.750	1-1/16-12	---
676-16D	1.000	1-5/16-12	---

## STRATOFLEX 680 90° ELBOW FLARED FITTINGS FOR 156 HOSE



Part No.	Tube O.D.	Thread	Price Ea.
680-3S	.188	3/8-24	---
680-4S	.250	7/16-20	---
680-5S	.312	1/2-20	---
680-6D	.375	9/16-18	---
680-8D	.500	3/4-16	---
680-10D	.625	7/8-14	---
680-12D	.750	1 1/16-12	---
680-16D	1.000	1 5/16-12	---

## STRATOFLEX 311 STRAIGHT FLARED FITTING FOR 193 HOSE



Part No.	Tube O.D.	Thread	Price Ea.
311-2D	.125	5/16-24	---
311-3D	.188	3/8-24	---
311-4D	.250	7/16-20	---
311-6D	.375	9/16-18	---
311-8D	.500	3/4-16	---
311-10D	.625	7/8-14	---

## STRATOFLEX 2650 FIRESLEEVE



Part No.	Use With Hose No.	*10781-4 Clamp	Price Per Ft.
2650-6	-4	-	-
2650-8	-6	-3	-4
2650-9	-	-4	-5
2650-10	-8	-4	-6
2650-11	-	-6	-
2650-12	-10	-5,-6	-8
2650-13	-	-8	-
2650-14	-12	-	-22CR
2650-16	-	-10	-10
2650-18	-	-	-12
2650-20	-16	-	-12
2650-22	-	-	-16

## STRATOFLEX FIRESLEEVE END DIP



Stratoflex 5027 Room temperature curing cement for Stratoflex Firesleeve. To use, dip each end of firesleeve in accordance with P-104-29 and applicable drawing. Always use current specifications.

P/N **5027**