GROVE MASTER BRAKE CYLINDERS



Clevis End—3/16" cylinder. Consider the following when shole, 1/4" wide slot proper master cylinder for your aircraft:



Eye Bolt End—3/16" hole, 1/2" head diameter



diameter

3.The attach type for the upper end (clevis, or eye bolt)4.The attach type for the lower end (cross drilled,

These master cylinders are the perfect choice for

all Grove brake systems as well as use with other

major brands that require a high pressure master cylinder. Consider the following when selecting the

1. The style (with or without integral reservoir, etc.)

2. The pin-to-pin length-this is the length between

the upper and lower attach holes.

slotted, etc.)



Cross Drilled - 3/16" holes inline with fitting and also 90° to fitting



90° Offset - 3/16" hole drilled 90° to fitting. Tab is inline with fitting.



Inline -3/16" hole drilled inline with fitting Tab is offset 90° to fitting



Slotted -0.090" slot inline with fitting. 3/16" hole drilled 90° to fitting.



Right Offset Tab 3/16" hole drilled 90° to fitting



Left Offset Tab 3/16" hole drilled 90° to fitting

Grove P/N	Our Part No.	Pin-to-Pin Length	Upper Attachment	Lower Attachment	Weight	Price
670-1	06-00594	7.5"	Clevis	Inline	5.9 oz.	
670-2	06-00866	8.0"	Clevis	Inline	6.2 oz.	
670-3	06-00104	7.5"	Clevis	90° Offset	5.9 oz.	
670-4	06-00869	8.0"	Clevis	90° Offset	6.2 oz.	
670-8	06-01286	7.25"	Clevis	90° Offset	5.9 oz.	
670-13	06-00871	8.0"	3/8" Eye Bolt	90° Offset	6.2 oz.	
670-14	06-00872	8.0"	3/8" Eye Bolt	Inline	6.2 oz.	
670-15	06-00596	8.0"	1/2" Eye Bolt	90° Offset	6.2 oz.	
670-16	06-00873	7.5"	1/2" Eye Bolt	90° Offset	5.9 oz.	
670-17	06-00597	8.0"	1/2" Eye Bolt	Inline	6.2 oz.	
670-18	06-00875	7.5"	1/2" Eye Bolt	Inline	5.9 oz.	
670-19	06-00877	7.5"	3/8" Eye Bolt	90° Offset	5.9 oz.	
670-20	06-00878	7.5"	3/8" Eye Bolt	Inline	5.9 oz.	

Grove P/N	Our Part No.	Pin-to-Pin Length	Upper Attachment	Lower Attachment	Weight	Price
671-20	06-00880	7.5"	1/2" Eye Bolt	Cross Drilled	5.9 oz.	
671-21	06-00882	7.5"	3/8" Eye Bolt	Cross Drilled	5.9 oz.	
671-22	06-00884	8.0"	1/2" Eye Bolt	Cross Drilled	6.2 oz.	
671-23	06-00887	8.0"	3/8" Eye Bolt	Cross Drilled	6.2 oz.	

Grove P/N	Our Part No.	Pin-to-Pin Length	Upper Attachment	Lower Attachment	Weight	Price
672-1	06-00889	5.0"	Clevis	Cross Drilled	4.0 oz.	
672-2	06-00891	5.5"	Clevis	Cross Drilled	4.2 oz.	
672-3	06-00893	6.0"	Clevis	Cross Drilled	4.5 oz.	


Grove P/N	Our Part No.	Pin-to-Pin Length	Upper Attachment	Lower Attachment	Weight	Price
673-9	06-00895	7.5"	Clevis	Cross Drilled	5.9 oz.	
673-10	06-00896	8.0"	Clevis	Cross Drilled	6.2 oz.	
673-11	06-00897	7.5"	1/2" Eye Bolt	Left Offset	5.9 oz.	
673-12	06-00898	7.5"	1/2" Eye Bolt	Right Offset	5.9 oz.	
673-13	06-00899	7.5"	1/2" Eye Bolt	Slotted 90°	5.9 oz.	
673-14	06-00901	7.5"	1/2" Eye Bolt	Slotted Inline	5.9 oz.	

Grove P/N	Our Part No.	Pin-to-Pin Length	Upper At- tachment	Lower Attachment	Weight	Price
674-1	06-00902	7.5"	Clevis	Cross Drilled	5.0 oz.	
674-2	06-00903	8.0"	Clevis	Cross Drilled	5.0 oz.	
674-3	06-00904	7.0"	Clevis	Cross Drilled	5.0 oz.	

Grove P/N	Our Part No.	Pin-to-Pin Length	Upper Attachment	Lower Attachment	Weight	Price
675-1	06-00097	8.0"	Clevis	Inline	8.1 oz.	
675-2	06-00905	7.5"	Clevis	Inline	7.9 oz.	
675-3	06-00593	8.0"	Clevis	90° Offset	8.1 oz.	
675-4	06-00906	7.5"	Clevis	90° Offset	7.9 oz.	
Grove P/N	Our Part No.	Pin-to-Pin Length	Upper Attachment	Lower Attachment	Weight	Price
Grove P/N 676-1					Weight 9.3 oz.	Price
	No.	Length	Attachment	Attachment		
676-1	No. 06-00907	Length 8.0"	Attachment Clevis	Attachment Inline	9.3 oz.	
676-1 676-2	No. 06-00907 06-00908	Length 8.0" 7.5"	Attachment Clevis Clevis	Attachment Inline Inline	9.3 oz. 9.0 oz.	

REMOTE BRAKE FLUID RESERVOIRS

Quality machined from 6061 billet. Top Normal installation requires is retained by snap ring with O-ring seal. Supplied with vented 1/8" NPT cap plug. Anodized for corrosion resistance.



Cylinder. 1.98" high; 1.38" diameter Designed to attach to firewall or other Holds 1.10 fluid ounces remote location. Adequate capacity Weighs 1.5 ounces. to serve both master cylinders. Outlet 067-050 has 1/8" female NPT thread at bottom

of reservoir. 067-054 P/N 06-00819 Normal installation requires two (one for each master cylinder.) Supplied with 1/8" NPT fitting. Attaches directly to your master cylinder. 1.98" high; 1.38" diameter Holds 1.10 fluid ounces Weighs 1.5 ounces. 067-050

P/N 06-00818



All master cylinders have a 5/8" bore, 1/8" NPT outlets, are rated at 1,000 psi for use with MIL-H-5606 hydraulic fluid.

WWW.AIRCRAFTSPRUCE.CA

LG

Reservoir Volume 3.05 cu-in P/N 676-1