Y-FIBER AIRCRAFT COAT



AIRCRAFT SPRUCE - WORLD'S LARGEST DISTRIBUTOR OF POLY-FIBER PRODUCTS

This FAA approved process utilizing Poly-Fiber Dacron polyester and the unique "Poly" line of finishes assures a beautiful, durable, weather-resistant cover job every time. Documented time tested results by the professionals. The Poly-Fiber Covering Process was issued Supplemental Type Certificate No. SA-1008-WE in 1965 and this number will apply to all aircraft.

Note: Formerly known as Stits covering process. Only Poly-Fiber materials may be used through the topcoat paint to comply with STC requirements. Poly-Fiber finishes are required for approval. Poly-Fiber is approved for use on most certified aircraft. To be sure, check the Master Eligibility List in the latest revision of Poly-Fiber Procedure Manual No. 1.




POLY-FIBER FABRIC UNCERTIFIED LIGHT

1.87 oz/sq. yard. Lightweight fabric recom-mended for covering ultralight aircraft. This fabric will be unstamped. It is not approved for certified aircraft except on plywood surface. 72" Width P/N 09-02001 /Lineal Yd.

MEDIUM WEIGHT

2.79 oz/sq. yard. Standard fabric recommended for normal service on all types of aircraft regardless of speed, wing loading or horsepower. P/N 09-01600 /Lineal Yd.

HEAVY DUTY



3.40 oz/sq. yard. Recommended for severe operating conditions and very high wing loading aircraft where a very tough, durable, low elongation, high tension fabric is required and weight is not critical. Great for agricultural, aerobatic and bush planes. 72" Width. P/N 09-01700 /Lineal Yd.

POLYESTER PADDING

Non -woven, 45" wide, 3 oz. per yard. Used under fabric on wing leading edge and turtle deck to smooth rough surfaces. P/N 09-01750

POLY-FIBER POLYESTER PINKED EDGE TAPES

Part No.	Style #	Roll Width	Roll Length	Price.
09-02200	Med.	1"	25 yds.	
09-02400	Med.	1-1/2"	25 yds.	
09-02450	Med.	2"	25 yds.	
09-02500	Med.	2"	50 yds.	
09-02900	Med.	3"	25 yds.	
09-03300	Med.	4"	25 yds.	
09-03350	Med.	6"	25 yds.	
09-02300	Light	1"	25 yds.	
09-02350	Light	1-1/2"	25 yds.	
09-02705	Light	2"	25 yds.	
09-02700	Light	2"	50 yds.	
09-03100	Light	3"	25 yds.	
09-03400	Light	4"	25 yds.	
09-03545	Light	6"	25 yds.	
09-03565	Bias	2"	25 yds.	
09-03570	Bias	3"	25 yds.	
09-03580	Bias	4"	25 yds.	

POLY-FIBER TAPES. CORD & THREAD

		ltem	Part No.	Yards Spool	Price
0.	Reinforcing Tape	3/8" Wide	09-03600-1	60	
		1/2" Wide	09-03700-1	60	
	Rib Lacing Cord	(Std. Round)	09-03800	296	
		Rib Cord, Flat	09-03810	500	
	Sewing Thread	Machine	09-03900	500	
		Hand	09-04000	250	
	Anti-Chafe	1" Wide	09-02110	30	

HEAVY INTER-RIB BRACING TAPE

Non-adhesive polyester twill tape for inter-rib bracing. Twice as strong as cotton tape. 36 yd. rolls.`1/2" WideP/N 09-40912

THE POLY-FIBER PRACTICE KIT



If you're thinking of building a fabric-covered airplane but are wondering what the covering process is like, this is the perfect answer. You get a practice frame, fabric, tapes, needles, rib lacing cord, thermometer, instructions, and all the coatings you need to work through the Poly-Spray stage. There's enough of everything to do the entire process twice. You'll see how easy and enjoyable fabric covering really is. P/N 09-06220



POLY-FIBER COLOR CHART #50

Note: These samples are an approximate computer representation of the actual color and are to be used for reference only. P/N 09-00234

POLY-FIBER SOLVENTS & CLEANERS



METL-SOL C-2200 METAL SURFACE CLEANER

A strong solvent blend formulated to remove oil, silicone, wax and other contaminants from all metal surfaces before priming. Not for painted surfaces. Quart.....P/N 09-40710 Gallon.....P/N 09-40720



C-2210 PAINT SURFACE CLEANER

A mild solvent blend formulated to remove oil, silicone, wax and other contaminants from all painted or primed surfaces. Also removes tape gum from painted surfaces and acrylic windshield materials.





310 ALKALINE DETERGENT CLEANER

Highly recommended as an alkaline metal cleaner for removing greases and oils. Also a very good cleaner for interior cabins and vinyl upholstery, as well as a wide variety of house-hold applications to remove waxes, dirt, and stains. Furnished as a concentrate for 32:1 dilution with water. Lemon scented and not harmful to your hands.

QuartP/N	310-QT
GallonP/N	310-1G



POLY-FIBER MEK

Solvent used to remove coatings for repairs, for clean up, and to release cemented seams. NOT used to thin or reduce any products.

Quart.....P/N 09-40835 GallonP/N 09-40845

WWW.AIRCRAFTSPRUCE.CA