MA ENGINE GAUGES



2-1/4 inch UMA Electronic Oil Pressure Gauge Case: Valox 420 Plastic Weight: 4.7 oz.

UMA 2-1/4" ELECTRONIC OIL PRESSURE 270°GAUGE

Electronic Oil Pressure Gauges connect to a pressure transducer and connects to the gauge with wires. Standard dial markings are black and white.

2-1/4", 0-60 PSI, TSO'd...P/N 10-02415 2-1/4", 0-80 PSI, TSO'd...P/N 10-02416 2-1/4", 0-100 PSI, TSO'd.P/N 10-02417 2-1/4", 0-100 PSIP/N 10-02424 2-1/4", 150 PSI......P/N 10-02761 SENDER NOT INCLUDED

SEE NEXT PAGE FOR SENDERS



DATCON OIL PRESSURE SENDER
Thread sizes: 1/8"-27 NPTF, #10-32 terminals, Common ground through mounting thread, 0-80 psi/0-5 bar range and 240-33.5 Ohms.P/N 10-05329



2-1/4 inch **UMA Electronic** Fuel Pressure Gauge Case: Valox 420 Plastic Weight: 4.7 oz.

UMA ELECTRONIC **FUEL PRESSURE 270°GAUGE** Electronic Fuel Pressure Gauges connect to a pres-

sure transducer and connects to the gauge with wires. Standard dial markings are black and white.

SEE NEXT PAGE FOR SENDERS



2-1/4 inch UMA Electronic Hydraulic Pressure Gauge Case: Valox 420 Plastic Weight: 4.7 oz.

UMA ELECTRONIC 2-1/4" HYDRAULIC PRESSURE 270° GAUGE

Electronic Hydraulic Pressure gauge connects to a precision, high pressure transducer which mounts directly to the aircraft's hydraulic system. Standard markings are black and white. 2-1/4", 0-2000 PSI, TSO'd......P/N 10-02459

> SENDER NOT INCLUDED SEE NEXT PAGE FOR SENDERS



2-1/4 inch **UMA Electronic** Oil Temperature Gauge Case: Valox 420 Plastic Weight: 4.8 oz.

UMA 2-1/4" ELECTRONIC OIL TEMPERATURE 270° GAUGE TSO'D

These rugged aircore gauges work with either thermocouple or thermister probes. Standard markings are black and white.

100-300° F, TSO'd......P/N 10-02443

SENDER NOT INCLUDED SEE NEXT PAGE FOR SENDERS



P/N 10-02057

UMA ELECTRONIC 2-1/4" CHT 270° GAUGE

These gauges are available for either thermocouple or thermistor probes. Standard markings are black and white

2-1/4", 100-300 °F - compatable with VDO P/N 10-02426

2-1/4", 100-600 °F - 90° sweep for use with thermocouple powered aircraft ... P/N 10-02429

2-1/4", 100-600 °F - 270° sweep for use with internal powered aircraft P/N 10-02057

TYPE J CHT PROBES

| 10mm Spark Plug Ring | P/N 10-00960 |
|------------------------|--------------|
| 12mm Spark Plug Ring | |
| 14mm Spark Plug Ring | |
| 18mm Spark Plug Ring | |
| 3/8"-24 Bayonet w/snap | |

UMA TSO'D TEMPERATURE PROBES

| T3B1 1/8 NPT TSP Type K with 6' Lead. | P/N | 10-05164 | |
|---------------------------------------|-----|----------|--|
| T3B2 3/8-24 TSO Type K with 6' Lead | P/N | 10-05165 | |
| T3B3 5/8-18 TSO Type Kwith 6' Lead | P/N | 10-05166 | |
| T3B3A 5/8-18 TSO Type Kwith 6' Lead | P/N | 10-05167 | |
| T3B11 1/4-18 TSO Type Kwith 6' Lead | | | |



UMA ELECTRONIC 2-1/4" WATER TEMPERATURE 270° GAUGE 2-1/4 inch UMA Electronic (UMA P/N T12212U300-

F000) Water Temperature Gauge Range: 100-300°F TSO2-1/4", 100-300°F TSO'd.

P/N 10-02428

UMA ELECTRONIC 2-1/4" CARBURETOR AIR **TEMPERATURE 270° GAUGE**

These gauges use either thermistor or electronic sensors. Standard markings are black and white. 2-1/4", -60-120 °F TSO'd... P/N 10-04670 2-1/4", -20-120 °F.............. P/N 10-02391





UMA TSO'D 2-1/4 CARBURATOR AIR TEMPERATURE GAUGE

TSO'd Carburetor Temperature 2 1/4" gauge. Range from -60 - 120°F. **Note:** This is the standard black and white gauge. For color range markings as shown you must add the color range markings part no. to your order.....P/N 10-03465

UMA Color Range Markings......P/N 10-02792



UMA 2-1/4" ELECTRONIC MANI-

FOLD PRESSURE 270° GAUGE Electronic Manifold Pressure gauges connect to a pressure transducer which connects to the aircraft's engine and indicates the absolute pressure in the intake manifold of the aircraft. These units are very precise and avoid plumbing issues. Standard markings are black and white.

.....P/N 10-02390 2-1/4", 5-50 IN/ HG...

SENDER NOT INCLUDED SEE NEXT PAGE FOR SENDERS



UMA 2-1/4" ELECTRONIC

OUTSIDE AIR TEMPERATURE
The digital Outside Air Temperature (O.A.T.) is available in either Fahrenheit or Celsius. Standard models use a Red LED display.

2-1/4", -40-60 °C, 270° P/N 10-02387 2-1/4", -40-140 °F, 270° P/N 10-02388

SENDER NOT INCLUDED SEE NEXT PAGE FOR SENDERS



UMA DUAL AMP/VOLTMETERS These 2-1/4" dual amp voltmeters are ideal for any aircraft where panel space is limited. Amperage is displayed at all times, and simply push a button to display voltage. Complete with gauge and shunt. Voltage range 0-30 volts.

Range: 30 amp......P/N 10-14680 60 amp.....P/N 10-14685 80 amp......P/N 10-14690 100 amp......P/N 10-14695

0-150 amp......P/N 10-00082 UMA Optional internal lighting......P/N 11-07239



AMMETERS

These new manufactured ammeters offer accuracy, rugged construction, and contemporary styling. Made in U. S. A. Furnished with shunt. Size: 2-1/4". Range: 0-30 (0 center).... P/N 10-14650

0-60 (0 center)....P/N 10-14655 0-80 (0 center)....P/N 10-14660 0-100 (0 center).. P/N 10-02788



REPLACEMENT UMA AMMETER SHUNTS 30/60/80/100AMP

UMA Ammeter shunt 30AMP, 60AMP, 80AMP, and 100AMP.

Shunt 30AMP 1C1P/N 10-02072 Shunt 60AMP Shunt 100AMP 1C4......P/N 10-02074



UMA 24/28v & 12/14v DC TO 120 VAC/400 hz Light Inverter large capacity. Non FAA/PMA 12/14 Volt.....P/N 10-07131 24/28 Volt......P/N 10-07132

UMA OPTIONAL INTERNAL LIGHTING

Optional internal lighting for all UMA 2-1/4", 3-1/8" instruments (except altimeter). This is just a lighted option. Order the instrument in addition to the internal lighting.P/N 11-07239