

# CHERRY PULLING HEADS

## PULLING HEAD FOR CHERRYLOCK® A-RIVETS H9055

**STEM SIDE EJECTION:** H9055 series pulling heads are available for installation of 3/32", 1/8", 5/32" and 3/16" diameter locked spindle CherryLOCK® 'A' code rivets in all materials, head styles and grip lengths. Stems are ejected from the side of the pulling head.

H9055-3: 3/32" .....	P/N 12-03132
H9055-4: 1/8" .....	P/N 12-03133
H9055-5: 5/32" .....	P/N 12-03134
H9055-6: 3/16" .....	P/N 12-03135

## CHERRY® MS STRAIGHT PULLING HEADS H9040

Cherry MS Straight Pulling Heads - H9040 Series.

H9040-4C .....	P/N 12-03127
H9040-5C .....	P/N 12-03128
H9040-6C .....	P/N 12-03129
H9044-8C .....	P/N 12-03130

## OFFSET MAXIBOLT PULLING HEAD H856-6MB

Maxibolt Pulling Head. Offset head style. Maxibolt Diameters: 3/16".  
P/N 12-03112

## CHERRY® NUT PLATE PULLING HEADS H902

These pulling heads fit directly onto Cherry G902 and G746A Power Riveters.

Cherry P/N	Rivet Dia. Inches	Part No.	Price
H902-3NPR	-3 (3/32")	12-03125	---
H902-4NPR	-4 (1/8")	12-03126	---

## CHERRY® FLUSH STYLE PULLING HEADS H9015

Flush style pulling heads will install both universal and countersunk rivets. These pulling heads fit directly onto Cherry G902-15 riveters.

H9015-3C .....	P/N 12-03121
H9015-4C .....	P/N 04-01515
H9015-5C .....	P/N 12-03123
H9015-6C .....	P/N 12-03124

## PULLING HEADS FOR CHERRYLOCK A-RIVETS H955

The H955 Series pulling heads fit directly on the G701A, G704B, G746A and G747 riveters. The heads in this series are capable of installing 3/32", 1/8", 5/32" and 3/16" diameter rivets in all materials and head styles and grip lengths. Stems feed through the pulling head and are ejected out the back of the tool.

H955-3: 3/32" .....	P/N 12-03136
H955-4: 1/8" .....	P/N 12-03137
H955-5: 5/32" .....	P/N 12-03138
H955-6: 3/16" .....	P/N 12-03139

## COMPACT UNIVERSAL HEAVY DUTY PULLING HEAD HD800

Description	Part No.	Price
HD800-6MB Installs Maxibolt -6 "S" type Cherry	12-03140	---
HD800-6MBU Installs Maxibolt -6 "U" type / "S" type AFS	12-03141	---
HD800-8MB Installs Maxibolt -8 "S" type	12-03144	---
HD800-8MBU Installs Maxibolt -8 "U" type	12-03145	---
HD800 Installs CherryMAX "AB" -8 (all materials) 8 Dia. MB Plus	12-03142	---
HD800-8A Installs Cherrylock "A" code	12-03143	---

## CHERRY OFFSET PULLING HEAD H782

The Cherry® brand H782 is a new universal, off-set pulling head capable of installing a broad variety of pull-type fasteners. Its strength, light weight and compact dimensions make it ideal for a diverse range of applications including restricted spaces. The H782 is capable of installing CherryMAX rivets, CherryLOCK 'A' code rivets, MaxiBolt 'S' type blind bolts, MBC rivets, SPR rivets, NAS1398 A & AB code products, MS90353/4, MS21140/1, 4, 5, NAS1719, 1720 & 1721 and pull-through type nut plate rivets. **Note:** Uses CherryMAX mounting system (G704B, G746A, G747).  
P/N 12-03091

## MAXIBOLT STRAIGHT PULLING HEADS

For use with G83 & G84 tools. For use with Cherry shift washer type only.

H83B-6MB .....	P/N 12-03101
H84A-8MB .....	P/N 12-03107
H84C-8MB .....	P/N 12-03110

## MAXIBOLT PULLING HEAD H84B-568

Maxibolt Pulling Head. Straight head style. Maxibolt Diameters: 5/32", 3/16".  
P/N 12-03109

## MAXIBOLT PULLING HEAD (S TYPE) H744

Cherry P/N	Head Style	MaxiBolt Dia.	Part No.	Price
H744-5MB	Straight	5/32"	12-03085	---
H744-6MB	Straight	3/16"	12-03086	---

## MAXIBOLT U-TYPE PULLING HEAD

Pulling heads to install "U" type Maxibolts®. Will fit G83 or G84-LS (w/744-700 adaptor).

H83B-5MBU .....	P/N 12-03099
H83B-6MBU .....	P/N 12-03102
H84A-8MBU .....	P/N 12-03108
H84C-8MBU .....	P/N 12-03111

## MAXIBOLT® PULLING HEAD (S TYPE) H652-8MB

Cherry MaxiBolt Pulling Head (S Type): Head Style - Straight, MaxiBolt Diameter - 1/4"  
P/N 12-03067

## MAXIBOLT RIGHT ANGLE PULLING HEAD H828

This pulling head aids installation of MAXIBOLTS in limited access applications. For use with G744 tool. For use with Cherry shift washer type only. Use 744-200 adapter for G83/G84.

Cherry P/N	Head style	Rivet Dia. Inches	Part No.	Price
H828-5MB	Right Angle	5/32"	12-03094	---
H828-6MB	Right Angle	3/16"	12-03095	---
H828-8MB	Right Angle	1/4"	12-03097	---

## RIGHT ANGLE PULLING HEAD H690-4C

H690-4C pulling head. 1/8" rivet diameter. Countersunk Head.  
P/N 12-03082

## PULLING HEAD FOR CHERRYLOCK® "A" CODE RIVETS H9044-8

These heads fit directly on the G55, G86, both obsolete and G740 Cherry® power riveters. Will fit on the G784 and G689 hydro-shift Cherry® riveters with the 680B57 adapter. For the 1/4" Cherrylock "A" rivets. 8 Diameter. ....P/N 12-03131

## CHERRYMAX STRAIGHT PULLING HEAD H846A-456

This pulling head installs 1/8", 5/32" & 3/16" Nominal & Oversize CherryMAX Rivets (G744 only) .....P/N 12-03103

## CHERRYMAX RIGHT ANGLE PULLING HEAD H828-8

CherryMAX Right Angle Pulling Head installs 1/4" Nominal & Oversize CherryMAX Rivets (G744 only) .....P/N 12-03096

## CHERRYMAX OFFSET PULLING HEAD H827-8

CherryMAX Offset Pulling Head installs 1/4" Nominal & Oversize CherryMAX Rivets (G744 only) .....P/N 12-03093

## CHERRYLOCK® RIGHT ANGLE PULLING HEADS H886

The H886 series right angle s fit directly on the G701A, G704B, G746A and G747 power riveters to install CherryLOCK® 'A' brand rivets in 3/32", 1/8", 5/32" and 3/16" diameters in all materials, head styles and up to -04 grip length.

H886-3 .....	P/N 12-03113
H886-4 .....	P/N 12-03114
H886-5 .....	P/N 12-03115
H886-6 .....	P/N 12-03116

## OFFSET LOCKBOLT PULLING HEADS H562-6B/8B

The H562 series pulling heads. Requires adapter (744-100) when used on the Cherry G84 tool.

-6 Diameter 3/16" .....	P/N 12-03059
-8 Diameter 1/4" .....	P/N 12-03060